


203003 HYDROLINE 13 PERFORMANCE LED



- High-corrosion resistance die-cast aluminum body
- Polyester painting with phosphocromating pre-finish
- **Stainless steel frame AISI 304**
- Stainless steel screws
- Stainless steel housing for recess included
- Clear tempered glass
- **CREE LED "XP-G2"**
- **19.5 WATT**
- **Lumen output: 1.950 lm**
- Electronic driver 220/240V 50/60Hz included
- Silicone rubber gasket
- Max static weight resistance 5.000 Kg
- **Protection against impact IK10 (20 joule)**
- Double cable-gland PG13.5
- 1 m power cable included



19.5 WATT	LIGHT BEAM OPTIONS	BULB FEATURES	LIGHT COLOURS	AVAILABLE COLOURS
190V... 250V/AC 50-60HZ	SPOT 10° 30° 45° (ON REQUEST)	HIGH-POWER LED	6000° K COLD WHITE 3000° K WARM WHITE BLUE	STAINLESS STEEL
IP67 - CE ▽ ⊕				
7,00 KG UNIT GROSS WEIGHT				

WHEN INSTALLING HYDROLINE, A "DRAINAGE BED" OF AT LEAST 20 CENTIMETERS HAS TO BE OBSERVED UNDER THE STAINLESS STEEL RECESSING BOX (GRAVEL AND SAND)

